E-150 RS 29ER

EMTB TRAIL / ENDURO 29ER SUSPENSION

UK SRP £5,999

PART CODE - WE150RST(SIZE)V2

Computer generated image - to illustrate colourway only



Uncompromised Whyte OTO geometry combined with an ultra-low centre of gravity means outstanding handling, balance and control. A complete eSystem from Bosch means reliability and unbeatable backup. Our "slide in" battery fitment means maximum structural integrity for minimum weight and torsional rigidity.

The high-torque 85Nm Bosch Performance Line CX motor is super-compact with exceptionally smooth power delivery which simulates normal pedalling, and range anxiety shouldn't be an issue as we fit a powerful 625Wh battery as standard.

Each one of our eMTBs delivers more fun in your ride than any other bike we have ever made.

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
Medium	64.7	74.9	611	341	814
Large	64.7	74.7	641	341	828
Extra Large	64.7	74.5	676	341	828
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Medium	1230	445	30.9	120	431.8
Large	1261	445	30.9	133	457.2
Extra Large	1298	445	30.9	148	482.6





Colour Matt Moss with Chalk & Ocean Sizes Available 6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing and 12mm X Frame 148mm Boost Dropouts RockShox ZEB Select RC 29". 150mm Travel, 44mm Offset, DebonAir, Charger 2 RC Damper, Fast Black Coating, Tapered Fork Steerer, 110mm x 15mm Boost, Maxle Ultimate RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound, 2 position compression adjustment Rear Shock FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings Headset Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 9 deg Micro Engagement 4 Pawl, 32 Rear Hub Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole Front Hub Spokes DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples Rims WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole Maxxis Assigai WT, TR, 29" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR II WT, TR, 29" Tyres x 2.4" 2x120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear SRAM X01-E Eagle, Single Click, MMX, 12 Speed Shift Levers Front Derailleur N/A Rear Derailleur SRAM X01 Eagle, 12 Speed Cassette SRAM XG-1275 Eagle, 10-52, 12 Speed Chain SRAM GX Eagle, 12 Speed Crankset SRAM EX1, 165mm, ISIS with X-SYNC 2. Direct Mount 36T for Bosch Performance Line CX, Black **Bottom Bracket** N/A Crank Bro High-Line 3, 30.9mm, M/L 150mm Travel, XL 170mm Travel, High-Line Ball Socket Remote Lever Seatpost Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail Seat Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide Bar Stem Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension Grips Whyte Lock-on Enduro Grip SRAM Code R. 4 Piston with Sintered Metal Pads. 220mm Disc Front Brakes SRAM Code R. 4 Piston with Sintered Metal Pads. 200mm Disc Rear Brakes SRAM Code R, MMX **Brake Levers** Pedals Indicates an upgrade or improvement over previous version Indicates an upgrade or improvement over the model below

Drive Unit	Performance CX 85Nm	
Battery	625Wh	
Battery Charger	4 Amp	
Display	Purion	
Dropout Code	SRAM UDH	
Shock Stroke and Sag Setting	50mm, Sag 14mm (25%) to 17mm (30%)	
Reducer Bush Widths	25mm x 8mm, no hardware at the rear	
Eye to Eye Length	210mm	