E-150 S 29ER

EMTB TRAIL / ENDURO 29ER SUSPENSION

UK SRP £5,499

PART CODE - WE150ST(SIZE)V2

Computer generated image - to illustrate colourway only



Uncompromised Whyte OTO geometry combined with an ultra-low centre of gravity means outstanding handling, balance and control. A complete eSystem from Bosch means reliability and unbeatable backup. Our "slide in" battery fitment means maximum structural integrity for minimum weight and torsional rigidity.

The high-torque 85Nm Bosch Performance Line CX motor is super-compact with exceptionally smooth power delivery which simulates normal pedalling, and range anxiety shouldn't be an issue as we fit a powerful 625Wh battery as standard.

Each one of our eMTBs delivers more fun in your ride than any other bike we have ever made.

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
Medium	64.7	74.9	611	341	814
Large	64.7	74.7	641	341	828
Extra Large	64.7	74.5	676	341	828
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Medium	1230	445	30.9	120	431.8
Large	1261	445	30.9	133	457.2
Extra Large	1298	445	30.9	148	482.6





			WHYTE	
		Colour	Matt Burnt Orange with Corn & Slate	
		Sizes Available	M,L,XL	
✓		Frame	6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing and 12mm X 148mm Boost Dropouts	
✓	Fork		RockShox ZEB 29", 150mm Travel, 44mm Offset, DebonAir, Charger R Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate	
		Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound, 2 position compression adjustment	
		Headset	FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings	
		Rear Hub	Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole	
\checkmark		Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole	
		Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples	
		Rims	WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole	
✓		Tyres	Maxxis Assigai WT, TR, 29" x 2,5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR II WT, TR, 29" x 2,4" 2x120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear	
		Shift Levers	SRAM GX-E, Eagle, Single Click, MMX, 12 Speed	
		Front Derailleur	N/A	
		Rear Derailleur	SRAM GX Eagle, 12 Speed	
		Cassette	SRAM PG-1210 Eagle, 11-50, 12 Speed	
		Chain	SRAM GX Eagle, 12 Speed	
\checkmark		Crankset	Whyte, forged alloy, 165mm, X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black	
		Bottom Bracket	N/A	
\checkmark		Seatpost	Whyte drop.it Adjust, 30.9mm, M/L 140-170mm Travel, XL 170-200mm Travel, MMX Paddle Remote Lever	
\checkmark		Seat	Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail	
		Bar	Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide	
		Stem	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension	
\checkmark		Grips	Whyte Lock-on Enduro Grip	
		Front Brakes	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 220mm Disc	
		Rear Brakes	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 200mm Disc	
		Brake Levers	SRAM Guide RE, MMX	
		Pedals	None	
√		Indicates an upgrade or improvement over previous version		
	✓	Indicates an upgrade or improvement over the model below		

Drive Unit	Performance CX 85Nm	
Battery	625Wh	
Battery Charger	4 Amp	
Display	Purion	
Dropout Code	SRAM UDH	
Shock Stroke and Sag Setting	50mm, Sag 14mm (25%) to 17mm (30%)	
Reducer Bush Widths	25mm x 8mm, no hardware at the rear	
Eye to Eye Length	210mm	