## E-160 RS EMTB TRAIL / ENDURO SUSPENSION

UK SRP £6,250

PART CODE - WE160RS(SIZE)V2

Bar

Stem

Grips

Front Brakes

Rear Brakes

**Brake Levers** 

Pedals

Computer generated image - to illustrate colourway only



Uncompromised Whyte OTO geometry combined with an ultra-low centre of gravity means outstanding handling, balance and control. A complete eSystem from Bosch means reliability and unbeatable backup. Our "slide in" battery fitment means maximum structural integrity for minimum weight and torsional rigidity.

The high-torque 85Nm Bosch Performance Line CX motor is super-compact with exceptionally smooth power delivery which simulates normal pedalling, and range anxiety shouldn't be an issue as we fit a powerful 625Wh battery as standard.

Each one of our eMTBs delivers more fun in your ride than any other bike we have ever made.

Size	Head Angle (adjustable to)	Seat Angle	Top Tube	BB Height (adjustable to)	Stand Over
Small	65.3 (64.7)	75.2	579.2	347 (339)	807
Medium	65.3 (64.7)	75.0	609.1	347 (339)	822
Large	65.3 (64.7)	74.8	638.3	347 (339)	822
Extra Large	65.3 (64.7)	74.6	667.8	347 (339)	824
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Small	1197.6	442	30.9	116	406.4
Medium	1228.5	442	30.9	130	431.8
Large	1258.6	442	30.9	142	457.2
Extra Large	1289.1	442	30.9	155	482.6





## Colour Matt Moss with Chalk & Ocean Sizes Available 6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape it Link and Frame 12mm X 148mm Boost Dropouts Fox Float 38, Performance 27.5", 160mm Travel, 44mm Offset with Grip Damper, 3pos Adjust and custom tune, Tapered Steerer, Fork 110mm x 15mm Boost, E-Thru Axle Fox Float Performance DPS, Evol LV, 3pos adjustable Compression and Rebound damping Rear Shock FSA No. 57E Orbit ZS. 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings Headset Rear Hub Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole Front Hub Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 32 Hole DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples Spokes WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole Rims Maxxis Assigai WT, TR, 27.5" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Terra, Dual Compound, Front, Maxxis Minion DHR WT, TR, Tyres 27.5" x 2.4" 120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear SRAM GX-E, Eagle, Single Click, MMX, 12 Speed Shift Levers Front Derailleur SRAM X01 Eagle, 12 Speed Rear Derailleur Cassette SRAM XG-1275 Eagle, 10-52, 12 Speed SRAM GX Eagle, 12 Speed Chain SRAM EX1, 165mm, ISIS with X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black Crankset **Bottom Bracket** Seatpost Crank Bro High-Line 3, 30.9mm, XS/S 125mm Travel, M/L 150mm XL 170mm Travel, High-Line Ball Socket Remote Lever Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail Seat

Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide

Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension

SRAM Code R, 4 Piston with Sintered Metal Pads, 220mm Disc

SRAM Code R. 4 Piston with Sintered Metal Pads. 200mm Disc

Whyte Lock-on Enduro Grip

Indicates an upgrade or improvement over previous version Indicates an upgrade or improvement over the model below

SRAM Code R. MMX

Drive Unit	Performance CX 85Nm
Battery	625Wh
Battery Charger	4 Amp
Display	Purion
Dropout Code	DROPWH18
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm