UK SRP £5,499

PART CODE - WE160S(SIZE)V2

Computer generated image - to illustrate colourway only




The E-160 S is available in 5 sizes from XS to XL. The RockShox ZEB 38mm stanchioned forks perfectly complement our proprietary OTO geometry for maximum steering control, and powerful Guide RE brakes keep the easy speed under control.

Uncompromised Whyte OTO geometry combined with an ultra-low centre of gravity means outstanding handling, balance and control. A complete eSystem from Bosch means reliability and unbeatable backup. Our "slide in" battery fitment means maximum structural integrity for minimum weight and torsional rigidity.

The high-torque 85Nm Bosch Performance Line CX motor is super-compact with exceptionally smooth power delivery which simulates normal pedalling, and range anxiety shouldn't be an issue as we fit a powerful 625Wh battery as standard.

Size	Head Angle (adjustable to)	Seat Angle	Top Tube	BB Height (adjustable to)	Stand Over
Extra Small	65.3 (64.7)	75.4	555.7	347 (339)	792
Small	65.3 (64.7)	75.2	579.2	347 (339)	807
Medium	65.3 (64.7)	75.0	609.1	347 (339)	822
Large	65.3 (64.7)	74.8	638.3	347 (339)	822
Extra Large	65.3 (64.7)	74.6	667.8	347 (339)	824
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Extra Small	1186	442	30.9	112	368.3
Small	1197.6	442	30.9	116	406.4
Medium	1228.5	442	30.9	130	431.8
Large	1258.6	442	30.9	142	457.2
Extra Large	1289.1	442	30.9	155	482.6





Colour Matt Diesel with Light Blue & Slate Sizes Available XS,S,M,L,XL 6061 Alloy, Hydro Formed T6 Aluminium, Multi Butted, Custom Drawn, Tapered Headtube, Internal Cable Routing, Shape it Link and Frame 12mm X 148mm Boost Dropouts RockShox ZEB 27.5", 160mm Travel, 44mm Offset, DebonAir, Charger R Damper, Fast Black Coating, Tapered Steerer, 110mm x Fork 15mm Boost, Maxle Ultimate RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound, 2 position compression adjustment Rear Shock FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings Headset Rear Hub Alloy, e-bike specific, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole Front Hub Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples Spokes WTB HTZ i30 TCS 2.0 System, Asymmetric, Sleeved Joint, Super Tough Construction, Tubeless Ready, 32 Hole Rims Maxxis Assigai WT, TR, 27.5" x 2.5" 120TPI, EXO+ Casing, 3C Maxx Grip, Dual Compound, Front, Maxxis Minion DHR II WT, TR, Tyres 27.5" x 2.4" 2x120TPI, Double Down, 3C Maxx Terra, Dual Compound, Folding Bead, Rear SRAM GX-E, Eagle, Single Click, MMX, 12 Speed Shift Levers Front Derailleur SRAM GX Eagle, 12 Speed Rear Derailleur Cassette SRAM PG-1210 Eagle, 11-50, 12 Speed SRAM GX Eagle, 12 Speed Chain SRAM EX1, 165mm, ISIS with X-SYNC 2, Direct Mount 36T for Bosch Performance Line CX, Black Crankset **Bottom Bracket** Seatpost Whyte drop.it Adjust, 30.9mm, XS/S 120-150mm Travel, M/L 140-170mm Travel, XL 170-200mm Travel, MMX Paddle Remote Fizik Terra Aidon, 145mm wide, Wingflex, S-Alloy Mobius rail Seat Whyte Custom 6061 Alloy, 30mm Rise, 35mm Bar Bore, 780mm Wide Bar Stem Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension Grips Whyte Lock-on Enduro Grip SRAM Guide RE, 4 Piston with Sintered Metal Pads, 220mm Disc Front Brakes SRAM Guide RE, 4 Piston with Sintered Metal Pads, 200mm Disc Rear Brakes SRAM Guide RE, MMX **Brake Levers** Pedals Indicates an upgrade or improvement over previous version

Drive Unit	Performance CX 85Nm			
Battery	625Wh			
Battery Charger	4 Amp			
Display	Purion			
Dropout Code	DROPWH18			
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)			
Reducer Bush Widths	25mm x 8mm, no hardware at the rear			
Eye to Eye Length	210mm			

Indicates an upgrade or improvement over the model below