

T-140C R

T-140 TRAIL SUSPENSION - 140MM

UK SRP £3,399



Computer generated image - to illustrate colourway only



The T-140 platform is all about maximum fun, wherever you ride. A versatile all-rounder with big-hit capabilities, it combines climbing efficiency with a hooligan attitude to descents, using every bit of its 140mm of suspension travel to keep you grinning from ear to ear.

The T-140 OTO geometry was designed around a shorter 37mm offset fork. The extra front end grip this creates allows us to make the most of the 140mm travel fork, fully exploiting the capabilities of the chassis, the more neutral handling and the 2.6" tyres.

The T-140 C R features our best and latest geometry and a premium carbon frame. Spec highlights include a SRAM GX Eagle drive-train combined with RockShox's new Pike Select RC Fork with Debonair and Charger RC damper.

PART CODE - WT140CR(SIZE)V2

	Colour	Matt Burnt Orange with Corn & Slate
	Sizes Available	S,M,L,XL
✓	Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, ISCG, 2 Bolt Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
	Fork	RockShox Pike Select RC 27.5", 140mm Travel, 37mm Offset, DebonAir, Charger RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
	Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
✓	Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
	Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
	Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
	Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
	Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
✓	Tyres	Maxxis Minion DHF TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Dissector TR 27.5" x 2.6" 60TPI, EXO+ Sidewall Protection, Rear
	Shift Levers	SRAM GX Eagle, MMX Clamp, 12 Speed
	Front Derailleur	N/A
	Rear Derailleur	SRAM GX Eagle, 12 Speed
	Cassette	SRAM PG-1230 Eagle, 11-50, 12 Speed
	Chain	SRAM GX Eagle, 12 Speed
	Crankset	SRAM X1 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
	Bottom Bracket	SRAM DUB, BSA, 73mm
	Seatpost	Whyte drop.it II Adjust, 30.9mm, S/M 120-150mm Travel, L/XL 140-170mm Travel, Paddle Remote Lever
	Seat	Whyte Custom, Dual Density, Triple Panel Design
	Bar	Whyte 6061 Alloy, 31.8mm, S 15mm Rise, 760mm Wide, M/L/XL, 30mm Rise 780mm Wide
	Stem	Whyte Gravity Stem, 35mm Extension
✓	Grips	Whyte Lock-on Enduro Grip
	Front Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc
	Rear Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc, Internal Routing
	Brake Levers	SRAM Guide G2 R, Matchmaker
	Pedals	None
✓	Indicates an upgrade or improvement over previous version	
✓	Indicates an upgrade or improvement over the model below	

Size	Head Angle (adjustable to)	Seat Angle	Top Tube	BB Height (adjustable to)	Stand Over
Small	65.9 (65.3)	74.7	583	330 (322)	796
Medium	65.9 (65.3)	74.5	612	330 (322)	802
Large	65.9 (65.3)	74.3	640	330 (322)	808
Extra Large	65.9 (65.3)	74.1	669	330 (322)	815
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
Small	1168	435	30.9	112	406.4
Medium	1198	435	30.9	125	431.8
Large	1228	435	30.9	140	457.2
Extra Large	1256	435	30.9	150	482.6

Dropout Code	DROPH18
Shock Stroke and Sag Setting	50mm, Sag 13mm (25%) to 16mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm