

T-160 S

T-160 TRAIL / ENDURO SUSPENSION - 160MM

Model	T-160 S
Model Group	T-160 Trail / Enduro Suspension - 160mm
UK SRP	£3,399.00
Whyte Part Code	WT160S(size)V2
Colour	Matt Moss with Rose & Chalk
Sizes Available	M,L,XL
Frame	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube, ISCG 2 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	RockShox Lyrik Select RC 29", 160mm Travel, 42mm Offset, DebonAir, Charger RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 57E Orbit ZS, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Assegai TR 29" x 2.5" 60TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Minion DHR II TR 29" x 2.4" WT 60TPI, EXO+ Sidewall Protection, Dual Compound, Rear
Shift Levers	SRAM GX Eagle, MMX, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle, 12 Speed
Cassette	SRAM PG-1230 Eagle, 11-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM X1 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte drop.it Post II Adjust, 30.9mm, M/L 140-170mm Travel, XL 170-200mm Travel, Shimano Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte Custom 6061 Alloy, 30mm Rise, 31.8mm, 780mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 200mm Disc
Rear Brakes	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 200mm Disc
Brake Levers	SRAM Guide RE, MMX
Pedals	None

Drive Unit	
Battery	
Battery Charger	
Display	
Dropout Code	SRAM UDH
Shock Stroke and Sag Setting	55mm, Sag 14mm (25%) to 17mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm