

# G-180 S MX

## G-180 GRAVITY / ENDURO SUSPENSION

<b>Model</b>	G-180 S MX
<b>Model Group</b>	G-180 Gravity / Enduro Suspension
<b>UK SRP</b>	£3,299.00
<b>Whyte Part Code</b>	WG180S(size)V2
<b>Colour</b>	Matt Granite with Chalk & Rose
<b>Sizes Available</b>	S,M,L,XL
<b>Frame</b>	6061 Alloy, SCR Aluminium Front Triangle with Tapered Head Tube, ISCG 2 Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
<b>Fork</b>	RockShox ZEB 29", 180mm Travel, 44mm Offset, DebonAir, Charger 2.1 R Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
<b>Rear Shock</b>	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound, 2 position compression adjustment
<b>Headset</b>	FSA No. 57 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
<b>Rear Hub</b>	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
<b>Front Hub</b>	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
<b>Spokes</b>	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
<b>Rims</b>	WTB 27.5" rear, 29" front ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
<b>Tyres</b>	Maxxis Assegai WT, TR, 29" x 2.5" 60TPI, EXO+ Sidewall Protection, 3C MaxxGrip, Dual Compound, Folding Bead, Front, Maxxis Minion DHR WT, TR, 27.5" x 2.4" WT 120TPI, Double Down Casing, 3C MaxxTerra, Rear
<b>Shift Levers</b>	SRAM SX Eagle, MMX, 12 Speed
<b>Front Derailleur</b>	N/A
<b>Rear Derailleur</b>	SRAM NX Eagle, 12 Speed
<b>Cassette</b>	SRAM PG-1210 Eagle, 11-50, 12 Speed
<b>Chain</b>	SRAM Eagle, 12 Speed
<b>Crankset</b>	SRAM Descendant 6K Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
<b>Bottom Bracket</b>	SRAM DUB, BSA, 73mm
<b>Seatpost</b>	Whyte drop.it II Adjust, 30.9mm, S 120-150mm Travel, M/L 140-170mm Travel, XL 170-200mm Travel, Paddle Remote Lever
<b>Seat</b>	Whyte Custom, Dual Density, Triple Panel Design
<b>Bar</b>	Whyte Custom 6061 Alloy, 20mm Rise, 35mm Bar Bore, 800mm Wide
<b>Stem</b>	Whyte Enduro Stem, 35mm Bar Bore, 35mm Extension
<b>Grips</b>	Whyte Lock-on Enduro Grip
<b>Front Brakes</b>	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 220mm Disc
<b>Rear Brakes</b>	SRAM Guide RE, 4 Piston with Sintered Metal Pads, 200mm Disc
<b>Brake Levers</b>	SRAM Guide RE, MMX
<b>Pedals</b>	None

<b>Drive Unit</b>	
<b>Battery</b>	
<b>Battery Charger</b>	
<b>Display</b>	
<b>Dropout Code</b>	SRAM UDH
<b>Shock Stroke and Sag Setting</b>	65mm, Sag 16mm (25%) to 19mm (30%)
<b>Reducer Bush Widths</b>	25mm x 8mm, no hardware at the rear
<b>Eye to Eye Length</b>	230mm