

T-140C R

T-140 TRAIL SUSPENSION - 140MM

Model	T-140C R
Model Group	T-140 Trail Suspension - 140mm
UK SRP	£3799
Whyte Part Code	WT140CR(size)V2
Colour	Matt Burnt Orange with Corn & Slate
Sizes Available	S,M,L,XL
Frame	Carbon, Uni-directional Multi Monocoque Front Triangle with Internal Cable Routing, Tapered Head Tube, ISCG, 2 Bolt Guide Mounts, Alloy Symmetrical SCR Rear Triangle, Shape.it and 148mm Boost Dropouts
Fork	RockShox Pike Select RC 27.5", 140mm Travel, 37mm Offset, DebonAir, Charger RC Damper, Fast Black Coating, Tapered Steerer, 110mm x 15mm Boost, Maxle Ultimate
Rear Shock	RockShox Deluxe Select + RT, DebonAir, Fast Black Coating, Adjustable Rebound and 2 Position Compression
Headset	FSA No. 42 Orbit ZS Plus, Integrated, 1 1/2" Lower and 1 1/8" Upper Sealed Cartridge Bearings
Rear Hub	Alloy, Double Sealed Cartridge Bearings, 12mm x 148mm Boost Thru Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearings, 15mm x 110mm Boost Thru Axle, 31mm Torque Caps, 32 Hole
Spokes	DT Swiss Champion 2.0mm, Black Stainless, Brass Nipples
Rims	WTB ST i30 TCS 2.0 System, Pinned Joint, Tubeless Ready, 32 Hole
Tyres	Maxxis Minion DHF TR 27.5" x 2.6" 120TPI, EXO Sidewall Protection, 3C Maxx Terra, Front, Maxxis Dissector TR 27.5" x 2.6" 60TPI, EXO+ Sidewall Protection, Rear
Shift Levers	SRAM GX Eagle, MMX Clamp, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM GX Eagle, 12 Speed
Cassette	SRAM PG-1230 Eagle, 11-50, 12 Speed
Chain	SRAM GX Eagle, 12 Speed
Crankset	SRAM X1 Eagle, X-SYNC 2, Direct Mount 32T, DUB, 170mm, Boost, 12 Speed
Bottom Bracket	SRAM DUB, BSA, 73mm
Seatpost	Whyte drop.it II Adjust, 30.9mm, S/M 120-150mm Travel, L/XL 140-170mm Travel, Paddle Remote Lever
Seat	Whyte Custom, Dual Density, Triple Panel Design
Bar	Whyte 6061 Alloy, 31.8mm, S 15mm Rise, 760mm Wide, M/L/XL, 30mm Rise 780mm Wide
Stem	Whyte Gravity Stem, 35mm Extension
Grips	Whyte Lock-on Enduro Grip
Front Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc
Rear Brakes	SRAM Guide G2 R, 4 Piston, 180mm Disc, Internal Routing
Brake Levers	SRAM Guide G2 R, Matchmaker
Pedals	None

Drive Unit	
Battery	
Battery Charger	
Display	
Dropout Code	DROPWH18
Shock Stroke and Sag Setting	50mm, Sag 13mm (25%) to 16mm (30%)
Reducer Bush Widths	25mm x 8mm, no hardware at the rear
Eye to Eye Length	210mm